

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-11. Cancelled

12. A pad assembly comprising:

a plurality of flexible sheets (42), each sheet being generally rectangular, of the same size and said sheets (42) having front (41) and rear (43) surfaces and peripheral edges including first (15) and second (16) opposite edges, said sheets having a band (40) of repositionable pressure sensitive adhesive coated on said rear surface (43) for adhering adjacent sheets together,

said band (40) being substantially parallel to the first (15) and second (16) edges and being spaced by a first predetermined spacing (1) from said first edge (15) and by a second predetermined spacing (2) from said second edge (16),

wherein the ratio between the first predetermined spacing (1) from the edge (19) of the band (40) closest to said first edge (15) to said first edge and the second predetermined spacing (2) from the edge (20) of the band (40) closest to said second edge to said second edge (16) is in the range of 0.1 to 10.

13. The pad assembly of claim 12, wherein said band (40) comprises a plurality of repositionable pressure sensitive adhesive stripes (45) being substantially parallel to the first (15) and second (16) edges and being spaced from neighboring stripes by areas (46) which comprise no adhesive.

14. The pad assembly of claim 12, wherein said band (40) of repositionable pressure sensitive extends continuously across the rear surface of said sheet between a first side edge (13) and a second side edge (14), which side edges are perpendicular to the first (15) and second (16) edge.

15. The pad assembly of claim 12, wherein the ratio between the spacing (1) from the edge (19) of the band (40) closest to said first edge (15) to said first edge and the spacing (2) from the edge (20) of the band (40) closest to said second edge to said second edge (16) is in the range of about 0.25 to 4.
16. The pad assembly of claim 12, wherein the width of the flexible sheets (42) is in the range of about 30 mm to 150 mm and the length of the flexible sheets (42) is in the range of about 30 mm to 200 mm.
17. The pad assembly of claim 12, wherein the ratio between the area of the rear side which is coated with adhesive to the area without adhesive is in the range of about 0.1 to 0.4.
18. The pad assembly of claim 12, wherein the ratio between the width (3) of the band (40) perpendicular to the first edge (15) and the sum of the first predetermined spacing (1) and the second predetermined spacing (2) is in the range of about 0.1 to 0.4.
19. The pad assembly of claim 12, further including a protective back sheet or back card having a front surface, the rear surface of the bottom most sheet in the pad being adhesively attached to the front surface of the back sheet or back card, and the front surface of the back sheet or back card being at least coextensive with the sheets in the pad.
20. The pad assembly of claim 12, wherein the band (40) of repositionable pressure sensitive adhesive is the only means which connects two adjacent sheets.
21. A method of applying an adhesive sheet to a surface, with the steps of:  
peeling an uppermost sheet from the pad assembly of claim 12 , and  
adhering said sheet to said surface.
22. A method according to claim 21, wherein said surface is generally vertical.